

(11)Publication number:

10~109253

TOKYO SEIMITSU CO LTD

(43)Date of publication of application: 28.04.1998

(51)Int.CI. B230 17/24 G01B 9/02 G01B 11/00

(21)Application number: 08-260690 (71)Applicant:


(22)Date of filing: 01.10.1996 (72)Inventor: **OSAWA NOBUYUKI**

(54) SYSTEM FOR MEASURING ERROR IN MOVEMENT OF MACHINE TOOL

(57)Abstract:

PROBLEM TO BE SOLVED: To easily conduct measuring work on the errors in th movement of a machine tool.

SOLUTION: A system for measuring errors in the movement of a machine tool, in which the movement errors of respective moving shafts of a machine tool 91 are measured by using a laser length measuring machine, is provided with such a rotating mechanism as rotates an interference optical unit of a laser length m asuring mahchine, which emits a measuring laser beam toward measuring corn r cubes 171, 172 fixed in the moving part, in correspondence to the xt rnal signal.



LEGAL STATUS

[Dat of request for examination]

11.12.1998

[Dat of sending the examiner's decision of rejection]

24.10.2000

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Dat of final disposal for application]

[Pat nt number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of

rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japanese Patent Office

(11)Publication number:

11-179636

(43)Date of publication of application: 06.07.1999

(51)Int.CI.

B23Q 17/09

(21)Application number: 09-349288

(71)Applicant:

TOSHIBA MACH CO LTD

(22)Date of filing:

18.12.1997

(72)Inventor:

TOKUYAMA HARUMICHI


ABE FUJIO

(54) REPLACEMENT TIMING DECISION SYSTEM FOR TOOL

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a replacement timing decision system of a tool which can be constitution by reducing a cost further with high

SOLUTION: A replacement timing decision system of a tool measuring the vibration of a rotary tool 31 having a cutting edge by a vibration sensor 51 to decide replacement timing of the rotary tool 31 is provided with a filter 53 separating a prescribed frequency band from a vibration sensor signal S3 output from the vibration sensor 51, taking means synchronizing with a trigger signal S2 of 1 pulse relating to one turn of the rotary tool 31 to take in the vibration sensor signal S3 through the filter 53, and a decision means deciding replac ment timing of the rotary tool 31 from the vibration sensor signal S3 taken in by this taking in means. The vibration sensor signal S3 is taken in synchronized with the rotation of the rotary tool 31, so that a vibration characteristic in according with a cutting edge position can be clearly detected.



LEGAL STATUS

[Dat of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's d cision of rejection or application converted registration]

[Dat of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of

r jection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japanese Patent Office